

BORN FOR SAFETY

Intrinsically Safe DMR Portable Two-way Radio

HP79XEx IIC



For workers in the Oil and Gas industry or firefighters in the Fire and Rescue, they operate in extreme conditions and take risks from explosive gas, combustible dusts, or chemical vapors. In the dangerous environments, safe, reliable, and high-efficient communication is paramount.

The HP79XEx IIC intrinsically safe DMR portable two-way radio leverages Hytera's 20 years of experience and expertise in explosion protection to take personal safety and mission-critical communications to a new level for the workers in oil and gas, mining, chemical, pharmaceuticals, and other industries with hazardous environments.

Certified with IECEx/ATEX, the HP79XEx IIC is the safest radio to keep the workers connected in hazardous environments without causing a fire or explosion. HP79XEx IIC has IS circuit, long-lasting explosion-proof battery, superior audio, extended radio coverage, and advanced ergonomics for easy operation.





Fire and Rescue

When firefighters make efforts to protect lives and properties in a place full of smoke, dust, and even toxic gas, the HP79XEx IIC provides safe and effective communications for them.



Oil and Gas

In dangerous environments with flammable liquid and explosive gas, the HP79XEx IIC ensures stable communications for operators to ensure their safety.



Mining

When miners work in complex coal wells with various explosive gases and combustible dust, such as methane, the HP79XEx IIC helps them stay connected and safe.




Manufacturing

In pharmaceutical processing, steel plant, food processing, and more industries where the chances of massive dust explosions are high, the HP79XEx IIC with a higher IS level can keep the workers safe by reliable communications.



Airport

In the airport with complex facilities that are exposed to fuels, the HP79XEx IIC offers the staff and on-site fire crew with instant and efficient communications.



Chemical Plant

In the chemical plant where the conversion and processing of flammable gases, liquids, and solids may lead to explosion, the HP79XEx IIC ensures stable communications for safe production.



ULTIMATE SAFETY

The HP79XEx IIC intrinsically safe radio is certified to standards listed by IECEx. It has been developed to provide safe and reliable communication in hazardous environments by adopting the new materials, brand-new structural design and innovative IS circuit. With optimized RF solution and pioneering audio solution, it extends communication range and provides better audio. Moreover, the HP79XEx IIC prepares for the unexpected before it really happens, thanks to lone worker, man down, and precise positioning.

IECEx

Ex ib I Mb
Ex ib IIC T4 Gb
Ex ib IIIC T120°C Db
IP66/IP67/IP68, $-25^{\circ}\text{C} \leq \text{Ta} \leq +60^{\circ}\text{C}$

ATEX

I M2 Ex ib I Mb
II 2G Ex ib IIC T4 Gb
II 2D Ex ib IIIC T120°C Db
IP66/IP67/IP68, $-25^{\circ}\text{C} \leq \text{Ta} \leq +60^{\circ}\text{C}$


US

Class I, Zone 1, AEx ib IIC T4 Gb
Zone 21, AEx ib IIIC T120°C Db
IP66/IP67/IP68, $-25^{\circ}\text{C} \leq \text{Ta} \leq +60^{\circ}\text{C}$

CA

Ex ib IIC T4 Gb
Ex ib IIIC T120°C Db
IP66/IP67/IP68, $-25^{\circ}\text{C} \leq \text{Ta} \leq +60^{\circ}\text{C}$






Explosion-proof Standard:
EU ATEX directive
and IECEx standards

Gas Group:
I: Methane (Mining)
IIA: Propane
IIB: Ethylene
IIC: Acetylene, hydrogen
(Hazard Level: IIC > IIB > IIA)

Classification for hazardous places
1: Very high level (zone 0 or zone 20)
2: High level (zone 1 or zone 21)
3: Normal level (zone 2 or zone 22)
Zone 0: present continuously
Zone 1: present intermittently
Zone 2: present abnormally



M1: Equipment must continue to operate in a potentially explosive environment.
M2: Equipment does not operate in a potentially explosive environment. (Hazard Level: M1 > M2)

Level of Protection:
ia: Intrinsically safe (Category M1/M2)
ib: Intrinsically safe (Category M2)



Born for Safety




Wider range of operation temperature (in Ex area)

Thanks to new explosion-proof materials and advanced mechanical design, the HP79XEx IIC is built to work under temperatures from -25°C to 60°C in explosion-prone areas. With stable and even heat dissipation, the HP79XEx IIC is engineered to work in the extreme conditions, bringing extra safety and efficiency to everyday work.



More powerful intrinsically safe circuit

The HP79XEx IIC adopts innovative silicone encapsulation technology to prevent liquid, inflammable dust, or explosive gas from intruding internal circuits. With multiple circuit protection mechanisms, the HP79XEx IIC strictly limits the electrical circuit's energy to a non-ignitable level during operation. Meanwhile, the circuit contributes to 2W TX power and 2-watt audio power, extending the communications distance and boosting the audio loudness.



More rock-solid IS battery

The IS battery is secured to the radio by battery protection plate and an anti-falling battery latch. Even if the HP79XEx IIC is dropped by accident, the battery will never become detached to avoid potential sparks in hazardous circumstances. In addition, the PT890Ex is forbidden to be used with non-original battery with prompt on screen and flashing red LED indicator, as the safety of life and property cannot be endangered by any risks.

More professional anti-static technology

Electrostatic discharges are a source of ignition in explosive risk areas. Taking this in mind, the HP79XEx IIC first adopts high-strength, explosion-proof materials to prevent static electricity on the surface. Then the HP79XEx IIC uses a dual-material technology to resist the build-up of static electricity. So the workers can freely use the HP79XEx IIC without worrying the threats to lives and properties from the brisk fire or massive explosion.





Reliable to Use



Rugged-tested trust

The HP79XEx IIC is certificated with IP6X and MIL-STD-810H after a whole list of reliability tests such as accelerated life testing, impact test for the radio with 2.4-inch screen, and drop test. It is rugged enough to withstand dust, shock, or sudden drop. The workers can use the radio whatever harsh environments they encounter.



Dual antimagnetic mechanism

In the area containing metallic compounds, the HP79XEx IIC resists magnetic metal dust and shavings from the environments to damage the speaker — ensuring more outstanding audio and longer service life. All lies in the dual antimagnetic mechanism.





Built for Personnel Safety



Lone worker

Lone Worker provides protection and reassurance for those who work alone especially in dangerous environments, such as oil pipeline walker. If the HP79XEx IIC senses that the worker does not make any operation within a preset time, this radio will automatically alarm and report the location to the companion or control center for help.




Man down

Man Down is ideal for emergency situation. If the worker has fallen or is unconscious, or is unable to move, the HP79XEx IIC automatically detects a sudden tilt towards the ground, and alarms and reports the location to the companion or control center for help. This is vital to prevent loss of life and dangers.



Precise positioning

With the built-in positioning module, the HP79XEx IIC supports the flexible combination of GPS, BDS, GLONASS and Galileo satellite systems. Also, the HP79XEx IIC enhances positioning accuracy down to one meter, thanks to the dual-frequency positioning technology. Such reliable and accurate location information helps find the worker in need of assistance quickly in emergencies.





HIGH EFFICIENCY COMMUNICATIONS

The HP79XEx IIC takes critical communications to a new level, with the efforts of Hytera Audio Lab, RF & Antenna Lab, Energy-efficient Lab, and UX Design Lab*. The HP79XEx IIC keeps the workers always connected, from superior audio quality to extended radio range. The HP79XEx IIC is always in uptime thanks to the long-lasting battery. Moreover, the HP79XEx IIC facilitates the usage and management in terms of versatile connectivity and easy-to-use design.

* Hytera Professional Lab.



Superior Audio Quality

Super loudness

Most explosion-prone environments are noisy, thus how to provide clear and loud audio is the key to ensure effective communication among team members. The HP79XEx IIC, with a lighter and slimmer body, has a 2W speaker to deliver louder audio to improve team collaboration and work efficiency.

Ultra Clarity

With cutting-edge audio processing technology adopted, the HP79XEx IIC delivers crisp, clear audio even in complex environments, ensuring more reliable mission-critical and business-critical communications.

AI-based noise cancellation

The HP79XEx IIC adopts the most advanced AI-based noise cancellation algorithm and gets machine learning behavior. After learning and training thousands of noise samples, the HP79XEx IIC can quickly separate the human voice from the noise, making the workers get the right commands from the first word.

Water-porting design

The speaker has a unique water-porting design that can automatically expel water from the speaker's acoustic cavity fast. Even in heavy downpours, the HP79XEx IIC can still deliver clear audio.

Automatic gain control

Automatic gain control (AGC) automatically increases or decreases microphone gain to ensure consistently loud and clear audio output, regardless of how softly or loudly the workers are talking into the microphone.

Howling suppression

Using the innovative howling suppression algorithm, the HP79XEx IIC eliminates a screeching feedback sound when two radios are too close, even 30 cm away from each other.





Long-lasting Battery

The standard 2150 mAh battery, together with the cutting-edge low power consumption technology, can outlast the shift. The workers can check the remaining battery and battery health on the radio and extend the battery life using the smart charger.



Extended Radio Range

Thanks to the new-designed powerful IS circuits and RF optimization solution, HP79XEx IIC features 2W transmitting power and industry-leading receiving sensitivity (0.16μV), providing more smooth communications even at a distance or in the edge area, further enhancing personal safety and work efficiency.



Versatile Connectivity



BT 5.3

The HP79XEx IIC can connect to wireless IS accessories* more quickly and stably, without the hassle of wires and cables. Moreover, the HP79XEx IIC can run the BT-based applications developed by the third party to meet more scenarios.



WLAN

The HP79XEx IIC facilitates remote management through the WLAN, such as programming*, upgrading*, and log management*. It is a smarter way to manage radios in batch without getting them back and forth between the field and the office, greatly reducing operational expenses.



NFC

The HP79XEx IIC can be easily recognized and managed via NFC tag as per actual requirements.

* Not provided by Hytera.
The radio adapts the third-party wireless IS accessories.

* Coming soon.

Easy to Use

About 390g (with standard battery and antenna)

- Comfortable for long-time grip

2.4-inch LCD screen

- Intuitive to operate the radio or view the info

Textured housing on the back

- Never slip down from your fingers



U-shaped groove

- Quick to attach and release the belt clip



Large LED indicator

- Easy to get the radio status

Vibration pattern

- Never miss any call and message



User-friendly UI

- 9-grid menu
- Conversational SMS interface
- Pop-up notification on home screen

Purpose-built knob and keys

- Volume/channel selector knob
- Enlarged emergency key
- Three programmable keys
- Tactile and textured keys
- Four navigation keys



At a Glance

LED Indicator

Channel/Volume Knob

Microphone

2.4-Inch Display

Accessory Connector

Speaker

Emergency Button

Battery Lock

Belt Clip Groove

Strap Hole

Programmable Key

PTT Key

Programmable Keys

NFC Tag

Li-ion Battery



SPECIFICATIONS

| General | |
|---------------------------------|---|
| Frequency Range | 400-480MHz 136-174MHz 350-400MHz |
| Channel Capacity | 1024 |
| Zone Capacity | 64 |
| Channel Spacing | 12.5kHz/20kHz/25kHz |
| Operating Voltage | 7.4V (rated) |
| Battery | 2,150 mAh IIC intrinsically safe Li battery (Typical) |
| Battery Life (5/5/90) | 24h (GNSS OFF) 21h (GNSS ON) |
| Frequency Stability | ±0.5ppm |
| Antenna Impedance | 50Ω |
| Dimensions (H x W x D) | 130 x 55 x 37mm |
| Weight (with antenna & battery) | about 390g |
| Display | 2.4 inch LCD, 320 x240 pixel, 262000 colors |
| Connectivity | BT 5.3 BLE+EDR/WLAN 2.4G/NFC: ISO/IEC 15693 |

| Receiver | |
|------------------------------|--|
| Sensitivity | Analog: 0.16μV(12dB SINAD) 0.14μV(Typical)(12dB SINAD) Digital: 0.16μV/BER5% |
| Adjacent Channel Selectivity | TIA-603: 60dB@12.5kHz; 70dB@20/25kHz ETSI: 60dB@12.5kHz; 70dB@20/25kHz |
| Intermodulation | TIA-603: 70dB@12.5/20/25kHz ETSI: 65dB@12.5/20/25kHz |
| Spurious Response Rejection | TIA-603: 70dB@12.5/20/25kHz ETSI: 70dB@12.5/20/25kHz |
| Blocking | TIA-603: 80dB ETSI: 84dB |
| Hum and Noise | 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz |
| Rated Audio Power Output | 0.5W |
| Rated Audio Distortion | ≤3% |
| Audio Response | +1 ~ -3dB |
| Conducted Spurious Emission | <-57dBm |

| Transmitter | |
|-----------------------------|---|
| RF Power Output | 2W/1W |
| FM Modulation | 11K0F3E@12.5kHz 14K0F3E@20kHz 16K0F3E@25kHz |
| 4FSK Digital Modulation | 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW |
| Conducted/Radiated Emission | -36dBm < 1GHz; -30dBm > 1GHz |
| Modulation Limiting | ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@25kHz |
| FM Hum & Noise | 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz |
| Adjacent Channel Power | 60dB@12.5kHz; 70dB@20/25kHz |
| Audio Response | +1 to -3dB |
| Audio Distortion | ≤3% |
| Digital Vocoder Type | AMBE+2™ |
| Digital Protoca | ETSITS102 361-1, -2, -3 |

| Environmental | |
|------------------------|--|
| Operating Temperature | -30°C to +60°C (in non-hazardous area) -25°C to +60°C (in hazardous area) |
| Storage Temperature | -40°C~ +85°C |
| ESD | IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air) |
| Dustproof & Waterproof | IP64/IP65/IP66/IP67/IP68 per IEC-60079-0:2017 & IEC-60529 |
| Humidity | MIL-STD-810H |
| Shock and Vibration | MIL-STD-810H |

| Location Services | |
|------------------------------------|---|
| GNSS | GPS, BDS, GLONASS, Galileo |
| TTFF(Time To First Fix) Cold Start | <35 seconds |
| TTFF(Time To First Fix) Hot Start | <1 second |
| Horizontal Accuracy | 1 m (dual-frequency GNSS, 95% probable, -130 dBm, ≥ 22 operational satellites) |

Accuracy specs are for long-term tracking (95th percentile values>5 satellites visible at a nominal -130dBm signal strength)

Standard Accessories



Battery (Standard Capacity)



Charger



Power Adapter



Antenna



Belt Clip



Strap

Optional Accessories



Remote speaker Microphone



Earpiece



Carry Case



Intrinsically Safe Hamlet Heavy Duty Noise-cancelling Headset kit



Intrinsically Safe and Adjustable Earset



Intrinsically Safe Large PTT



Hytera Communications Corporation Limited

Stock Code: 002583.SZ

Address: Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, P.R.C.

Tel: +86-755-2697 2999 **Fax:** +86-755-8613 7139 **Post:** 518057

Http: //www.hytera.com **marketing@hytera.com**



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd.
©2023 Hytera Communications Corp., Ltd. All Rights Reserved.